

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 324 586 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

02.07.2003 Bulletin 2003/27

(51) Int Cl.7: H04N 1/21

(21) Application number: 02028879.1

(22) Date of filing: 23.12.2002

(84) Designated Contracting States:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
IE IT LI LU MC NL PT SE SI SK TR

Designated Extension States:

AL LT LV MK RO

• Seo, Kang Soo

Dongan-gu, Anyang, Kyunggi-do, 431-075 (KR)

• Kim, Byung Jin

Bundang-gu, Sungnam,

Kyunggi-do, 463-010 (KR)

(30) Priority: 24.12.2001 KR 2001083903

(71) Applicant: LG ELECTRONICS INC.

Seoul 150-010 (KR)

(74) Representative: Schorr, Frank, Dr. et al

Diehl Glaeser Hiltl &amp; Partner,

Augustenstrasse 46

80333 München (DE)

(72) Inventors:

• Um, Soung Hyun

Anyang, Kyunggi-do, 431-050 (KR)

## (54) Method of recording still pictures onto a recording medium

(57) The present invention relates to a method of recording still pictures and audio data onto a rewritable recording medium. The present method records still-picture video and audio files of the recording format of a digital still camera under a subdirectory of a DCIM (Digital Camera Images) directory of DCF (Design rule for Camera File system) and still-picture video and/or audio files of the recording format of a disk video recorder under a subdirectory of a moving-picture directory, creates man-

agement information for searching and presentation control of the still-picture video and audio files below the DCIM directory and the still-picture video and/or audio files below the moving-picture directory, and records the created management information under another subdirectory of the moving-picture directory. Thus, efficient and convenient file management is possible through a single recording medium, which results in remarkable improvement of use convenience of a motion picture recorder and a digital still camera.




FIG. 2

EP 1 324 586 A1

1

EP 1 324 586 A1

2

**Description****BACKGROUND OF THE INVENTION****Field of the Invention**

[0001] The present invention relates to a method of recording still pictures and audio data onto a rewritable recording medium.

**Description of the Related Art**

[0002] A disk-type recording medium such as a compact disk (CD) can store high-quality digital audio data permanently, so that it is very popular recording medium. Recently, a digital versatile disk (referred as 'DVD' hereinafter) has been developed as a new disk-type recording medium. A DVD can store much larger size than a CD, thus, high-quality moving picture or audio data are recorded on a DVD for much longer time. Therefore, a DVD will be used widely in the near future.

[0003] There are three types of a DVD, DVD-ROM for read-only, DVD-R for write-once, and DVD-RAM or DVD-R/W for rewritable. For a rewritable DVD, the standardization of data writing format is being finished.

[0004] In these days, a digital TV broadcast being capable of carrying TV programs of HD (High-Definition) quality is in service. Thus, a new high-density recording medium is being developed to record digital TV programs of such quality. The new high-density recording medium targets about 23GBytes in storage capacity that is about five times of a DVD. Standardization of application specification of that recording medium is in progress among several related companies. If the high-density recording medium is commercialized in near future, motion picture data and many still pictures can be stored on a single high-density recording medium.

[0005] In addition, a Digital Still Camera (DSC) being capable of storing a taken picture in the form of digital data has been developed recently. Such a DSC usually has a memory chip of large storage capacity so that it can take high-quality pictures and store audio data associated with the stored pictures as well. In a DSC, the taken pictures are encoded in the format of JPEG, or TIFF while the audio data are done in the format of PCM, u-Law PCM, or IMA-ADPCM.

[0006] A DSC has a well-known file system called DCF (Design rule for Camera File system) for recording still pictures and audio data. Fig. 1 shows an illustrative DCF. In the structure of DCF, a DCIM (Digital Camera Images) directory exists under a root directory and many subdirectories may exist under the DCIM. Each subdirectory has 8-digit-long filename that is composed of three numeric digits and five character digits. The three numeric digits should be unique, for instance, one among 100~999, and the five character digits are arbitrarily chosen by a user. Because the three numeric digits are unique the subdirectories can be created up to

900.

[0007] A subdirectory, e.g., subdirectory '100ABCDE' of Fig. 1 can accommodate many data files of which filename is 8-digits long. The filename is composed of four numeric digits and four character digits. While the four character digits are chosen by a user the four numeric digits should be unique among data files if their attributes are different. The data files are still pictures and/or audio files, respectively. The still picture files have extension of 'JPG' or 'TIF' while the audio files encoded by PCM, u-Law PCM or IMA-ADPCM have extension of 'WAV'. The filenames of the data files can be same if their extensions are different. Therefore, when a picture file is to be index with audio, an index audio file can be linked with the picture file only if their filenames are made same.

[0008] By the way, a disk video recorder (DVR), which has been developed recently, can record still pictures and audio data as well as motion pictures onto a disk recording medium. If a DVR adopts its file recording structure being able to improve compatibility with a DSC for still picture and audio data, a user can move or copy between a DVR and a DSC without any data conversion or any data converting tool or with a very simple converting tool. This will improve use convenience of the two electronic machines remarkably.

**SUMMARY OF THE INVENTION**

[0009] It is an object of the present invention to provide several methods that record still pictures and audio data onto a recording medium for storing motion-picture data in a file structure compatible with DSC's file structure.

[0010] It is another object of the present invention to provide several methods enabling a file structure of a recording medium specified for motion picture data to accommodate still pictures and audio data.

[0011] A method of recording still pictures onto a recording medium in accordance with the present invention is characterized in that it comprises the steps of: recording still-picture video and audio files of a DSC's recording format under a subdirectory of the first directory and still-picture video and/or audio files of a DVR's recording format under a subdirectory of the second directory other than the first directory; creating management information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory and the still-picture video and/or audio files under the subdirectory of the second directory; and recording the created management information under another subdirectory of the second directory.

[0012] Another method of recording still pictures onto a recording medium in accordance with the present invention, is characterized in that it comprises the steps of: recording still-picture video and audio files under a subdirectory of the first directory; creating management

3

EP 1 324 586 A1

4

information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory; and recording the created management information under a subdirectory of the second directory.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The accompanying drawings, which are included to provide a further understanding of the present invention, illustrate the preferred embodiments of the invention, and together with the description, serve to explain the principles of the present invention, and wherein:

Fig. 1 shows an illustrative DCF (Design rule for Camera File system) adopted by a digital still camera;

Fig. 2 is a block diagram of a disk video recorder which a method of recording still pictures onto a rewritable recording medium in accordance with the present invention is embedded in; and

Figs. 3 to 11 show data recording structures of a motion-picture recording medium in accordance with respective embodiments of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0014] In order that the invention may be fully understood, a preferred embodiment thereof will now be described with reference to the accompanying drawings.

[0015] Fig. 2 is a block diagram of a disk device which a method of recording still pictures onto a rewritable recording medium in accordance with the present invention is embedded in.

[0016] The disk device of Fig. 2, e.g., a DVR can record video/audio data and management information for searching and reproduction control onto a rewritable recording medium.

[0017] The disk device comprises, as shown in Fig. 2, an input processing module, an output processing module, and a controller 19 conducting overall system control. The input processing module is composed of two input switching units 10 and 11, a still picture video 12 and a still picture audio encoder 13, a movie video 14 and a movie audio encoder 15, an MPEG 2 muxer 16, a formatter 17, and a DVR encoding DSP 18 while the output processing module is composed of two output switching units 30 and 31, a still picture video 32 and a still picture audio decoder 33, a movie video 34 and a movie audio decoder 35, an MPEG 2 demuxer 36, a parser 37, and a DVR decoding DSP 38.

[0018] The two input switching units 10 and 11 selectively connect their input signals to the still picture video 12 and the still picture audio encoder 13 or the movie video 14 and the movie audio encoder 15 in response

to a switching control 'CTL' of the controller 19. The still picture encoders 12 and 13 encode video data from the first switching unit 10 to JPEG or TIFF format and audio data from the second switching unit 11 to PCM, u-Law PCM, or IMA-ADPCM format, respectively as a DSC does.

[0019] The movie encoders 14 and 15 encode video data from the first switching unit 10 to MPEG 2 format and audio data from the second switching unit 11 to AC-3, MPEG 1 layer 2, or LPCM format, respectively. The MPEG 2 muxer 16 multiplexes the encoded video and audio data from the movie video 14 and the movie audio encoder 15 to produce MPEG 2 stream that is directed to the formatter 17.

[0020] In case that the encoded still picture video and audio data are inputted from the still picture encoders 12 and 13, the formatter 17 segments or groups input data to yield successive data units, adds necessary head information to each data unit, and transmits them sequentially to the DVR encoding DSP 18. The data unit has a size suitable for a recording unit area of a rewritable recording disk. The formatter 17 also produces management information for searching for and controlling reproduction of the re-sized still picture video and/or audio data. The produced management information is delivered to the controller 19.

[0021] In case that the encoded motion picture video and audio data are inputted from the movie encoders 14 and 15 and the MPEG 2 stream are from the MPEG 2 muxer 16 at the same time, the formatter 17 selects the encoded data or the MPEG 2 stream to segment or group the selected data to yield successive data units, adds necessary head information to each data unit, and transmits them sequentially to the DVR encoding DSP 18. The data unit has a size suitable for a recording unit area of a rewritable recording disk. The formatter 17 also produces management information for searching for and controlling reproduction of the re-sized motion picture video and/or audio data. The produced management information is delivered to the controller 19.

[0022] The DVD encoding DSP 18 constructs ECC (Error Correction Code) blocks with the successive data units having still or motion pictures and audio data and then modulates data of ECC blocks to corresponding recording waveforms that will form mark/space patterns on the surface of the rewritable recording disk. At this time, the controller 19 controls data recording of the DVR encoding DSP 18 in accordance with the data type being recorded. That is, the controller 19 determines recording location, file and directory to record data, and so on based data type being recorded. If needed, information entered by a user is used.

[0023] In addition, while or after video and/or audio data are recorded, the controller 19 records the management information received from the formatter 17 onto the rewritable recording disk through the DVR encoding DSP 18.

[0024] Below described are various file structures of

5

EP 1 324 586 A1

6

a rewritable recording medium that the above-explained recording processes are conducted onto.

[0025] Fig. 3 is a data recording structure of a motion-picture recording medium in accordance with the first embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is equivalent to DCF specified for a DSC.

[0026] In the recording structure of Fig. 3, there is a 'DVR' directory under a root directory. The 'DVR' directory is mandatory for motion picture recording of a disk video recorder. The 'DVR' directory has directories 'PLAYLIST', 'CLIPINF', 'STREAM', and so forth. The 'PLAYLIST' directory includes playlist files (\*.rpls, \*.vpls) containing motion-picture and still-picture play items and title management information. The directory 'CLIPINF' includes clip information files (\*.clpi) containing information on movie stream management and movie attribute and the directory 'STREAM' includes stream files (\*.m2ts) containing actual motion-picture data stream packets.

[0027] The DCF structure adopted by a DSC also exists under the root directory. That is, a DCIM directory is located under the root directory and many subdirectories may exist under the DCIM. Each subdirectory has 8-digit-long filename that is composed of three numeric digits and five character digits. The three numeric digits should be unique, for instance, one among 100~999, and the five character digits are arbitrarily chosen by a user. Because the three numeric digits are unique the subdirectories can be created up to 900.

[0028] A subdirectory, e.g., subdirectory '100ABCDE' of Fig. 1 can accommodate many data files of which filename is 8-digits long. The filename is composed of four numeric digits and four character digits. While the four character digits are chosen by a user the four numeric digits should be unique among data files if their attributes are different. The data files are still pictures and/or audio files, respectively. The still picture files have extension of 'JPG' or 'TIF' while the audio files encoded by PCM, u-Law PCM or IMA-ADPCM have extension of 'WAV'. The data files can be named same if their extensions are different. Therefore, when a picture file is to be indexed with sound, an index audio file containing that sound can be linked with the picture file only if their filenames are made same.

[0029] After still pictures and/or audio data are recorded as above, the controller 19 records, under the 'DVR' directory, management information for search and presentation control of the recorded files under the DCIM. That is, the controller 19 creates a still-picture management file (\*.stli) containing management information for search and presentation control of the still picture video and audio files under the 'STILLINF' subdirectory of the 'DVR' directory.

[0030] The still picture video files (\*.jpg, \*.tif) and audio files (\*.wav) are referred by information written in the still-picture management file (\*.stli) and can be made presentation in accordance with information written in

the management file.

[0031] In addition, the controller 19 can record dubbing audio files (\*.mp2, \*.ac3, \*.lpcm, \*.dwav) linked with a picture or pictures under a subdirectory 'STILLDUB' of the 'DVR' directory. Each dubbing audio file includes audio data encoded by MPEG1 layer 2, AC-3, or LPCM that is the encoding format of a DVR. In this case, management information for search and presentation control of the dubbed audio files is further included in the management file (\*.stli) under the subdirectory 'STILLINF'.

[0032] If a recording medium of which files are organized as Fig. 3 is inserted, the controller 19 examines title management information and all playlist files (\*.rpls, \*.vpls) including motion-picture/still-picture play items that are under the subdirectory 'PLAYLIST', first. Then, it reads a motion-picture stream file (\*.m2ts) under the subdirectory 'STREAM' indicated by a motion-picture play item chosen by a user and decodes out stream data contained in the stream file. This is a general motion-picture reproduction operation.

[0033] During the motion-picture reproduction, the controller 19 controls the DVR decoding DSP 38, the parser 37, and the movie video 34 and the movie audio decoder 35 appropriately. The output switching units 30 and 31 are also controlled by the controller 19 to select signals from the movie video 34 and the movie audio decoder 35 to output.

[0034] The controller 19 may refer to the still-picture management file (\*.stli) under the subdirectory 'STILLINF' based on which type of play item is included in the playlist files (\*.rpls, \*.vpls). In other words, the controller 19 searches for and presents sequentially still-picture video files and/or audio files, pointed by a still-picture play item, under a certain subdirectory of the DCIM directory with reference to information written in the still-picture management file. For conducting this presentation, the controller 19 controls the DVR decoding DSP 38, the parser 37, and the still-picture video 32 and the still-picture audio decoder 33 appropriately. The output switching units 30 and 31 are also controlled by the controller 19 to select signals from the still-picture video 32 and the still-picture audio decoder 33 to output.

[0035] If the still-picture management file (\*.stli) under the subdirectory 'STILLINF' indicates that a still-picture video file being decoded is associated with a dubbed audio file under the subdirectory 'STILLDUB', the controller 19 controls the DVR decoding DSP 38 and the parser 37 to reproduce that dubbed audio file as well.

[0036] As described before, if the file structure of Fig. 3 is adopted by a DVR for recording still-picture video and audio files onto a recording medium, the still-picture video and audio files in DCF structure on that recording medium can be read directly by a DSC. Furthermore, if still pictures taken and audio data recorded by a DSC are copied onto a recording medium without any change of their file scheme, those contents on the recording medium can be read by a DVR after searching them.

7

EP 1 324 586 A1

8

[0037] In the above embodiment, the length of each subdirectory name 'PLAYLIST', 'CLPIINF', 'STREAM', 'STILLINF', or 'STILLDUB' is not longer than eight, however, other length and name can be used.

[0038] Fig. 4 is a data recording structure of a motion-picture recording medium in accordance with the second embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is equivalent to DCF as the first embodiment of Fig. 3.

[0039] The second embodiment of Fig. 4 is different from the first embodiment of Fig. 3 in that audio data files, for example, dubbing audio files (\*.mp2, \*.ac3, \*.lpcm, \*.dwav) whose data are encoded by MPEG 1 layer 2, AC-3, or LPCM, which is the recording format of a DVR, exist under a certain subdirectory of the DCIM directory. In this case, each audio file is stored under a subdirectory including its associated still-picture file and is named with its associated still-picture file. The controller 19 creates a still-picture management file (\*.stl) further containing information for search and presentation control of audio files in every subdirectory and records it under the subdirectory 'STILLINF'.

[0040] Other structure and features not mentioned here are same with the first embodiment of Fig. 3.

[0041] Fig. 5 is a data recording structure of a motion-picture recording medium in accordance with the third embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is equivalent to DCF as the first embodiment of Fig. 3.

[0042] The third embodiment of Fig. 5 is different from the first embodiment of Fig. 3 in that still pictures are recorded under the subdirectory 'STILLDAT' of the 'DVR' directory in the DVR-recognizable formats, namely, I-picture format (\*.mpg) of MPEG standard, and picture-mixed MPEG 2 transport stream format (\*.m2ts) while audio data are also recorded thereunder in the file formats of real audio (\*.rau) and dubbing audio (\*.dau). In this embodiment, dubbing audio data that have not been written under a subdirectory of the DCIM directory in association with a picture or pictures may be written under the subdirectory 'STILLDAT'.

[0043] The controller 19 creates a still-picture management file (\*.stl) containing information for search and presentation control of still-picture files and audio files below the directories 'DVR' and 'DCIM' and records it under the subdirectory 'STILLINF' of the 'DVR' directory.

[0044] Thus, a DVR is able to search for and to present a still-picture video or a still-picture audio file below the directory 'DVR' or 'DCIM' with reference to the still-picture management file (\*.stl) under the subdirectory 'STILLINF' while a DSC is able to present still-picture files and/or audio files below the directory 'DCIM'.

[0045] The presentation operation for a recording medium of which file scheme is organized as Fig. 5 is conducted the same as explained for the first embodiment

of Fig. 3.

[0046] The contents of the real audio files (\*.rau) and the dubbing audio files (\*.dau) can be included in the still-picture video files of MPEG I-picture format (\*.mpg) or MPEG2 transport stream format (\*.m2ts) under the subdirectory 'STILLDAT'. In addition, dubbing audio data may be divided into one part being written below the directory 'DCIM' and the other part being written below the subdirectory 'STILLDAT'.

[0047] All of the files under the separate subdirectories 'STILLDAT' and 'STREAM' can be collected under a new integrated subdirectory. Each still-picture video file may be composed of a single picture.

[0048] Fig. 6 is a data recording structure of a motion-picture recording medium in accordance with the fourth embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is equivalent to DCF as the first embodiment of Fig. 3.

[0049] The fourth embodiment of Fig. 6 is different from the third embodiment of Fig. 5 only in that the audio files (\*.mp2, \*.ac3, \*.lpcm, \*.dwav) encoded by MPEG 1 layer 2, AC-3, or LPCM that are DVR's formats as well as wave audio files (\*.wav) encoded in PCM, u-Law PCM, or IMA-ADPCM are stored together under subdirectories of the directory 'DCIM'.

[0050] That is, audio files, for instance, dubbing audio files linked with picture files are recorded in DVR's recording format below the directory 'DCIM' of DCF structure.

[0051] The controller 19 creates a still-picture management file (\*.stl) further containing information for search and presentation control of files (\*.mpg, \*.m2ts, \*.rau, \*.dau) under the subdirectory 'STILLDAT' and audio files (\*.mp2, \*.ac3, \*.lpcm, \*.dwav) below the 'DCIM' directory and records it under the subdirectory 'STILLINF' of the 'DVR' directory.

[0052] Fig. 7 is a data recording structure of a motion-picture recording medium in accordance with the fifth embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is similar to DCF.

[0053] The fifth embodiment of Fig. 7 is different from the first embodiment of Fig. 3 only in that the directory 'DCIM' has been moved under the directory 'DVR' defined for a DVR. Therefore, only path information to point individual still-picture video or audio files is different in a still-picture management file (\*.stl) under the subdirectory 'STILLINF' from that of the first embodiment of Fig. 3. In this embodiment, recording and searching operations are conducted the same as in the first embodiment of Fig. 3.

[0054] Fig. 8 is a data recording structure of a motion-picture recording medium in accordance with the sixth embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is similar to DCF.

[0055] The sixth embodiment of Fig. 8 is different from

9

EP 1 324 586 A1

10

the second embodiment of Fig. 4 only in that the directory 'DCIM' has been moved under the directory 'DVR' defined for a DVR. Therefore, only path information to point individual still-picture video or audio files is different in a still-picture management file (\*.sti) under the subdirectory 'STILLINF' from that of the second embodiment of Fig. 4. In this embodiment, recording and searching operations are conducted the same as in the second embodiment of Fig. 4.

[0056] Fig. 9 is a data recording structure of a motion-picture recording medium in accordance with the seventh embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is similar to DCF.

[0057] The seventh embodiment of Fig. 9 is different from the fourth embodiment of Fig. 6 only in that the directory 'DCIM' has been moved under the directory 'DVR' defined for a DVR. Therefore, only path information to point individual still-picture video or audio files is different in a still-picture management file (\*.sti) under the subdirectory 'STILLINF' from that of the fourth embodiment of Fig. 6. In this embodiment, recording and searching operations are conducted the same as in the fourth embodiment of Fig. 6.

[0058] Fig. 10 is a data recording structure of a motion-picture recording medium in accordance with the eighth embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is not matched with DCF.

[0059] The eighth embodiment of Fig. 10 is different from the above-explained embodiments in that still picture files, audio files, and/or dubbing audio files are all accommodated in DVR's file structure. That is, still picture files (\*.sti), real audio files (\*.rau), and dubbing audio files (\*.dau) are all included in the subdirectory 'STILLDAT'. Those files are named by a DVR the same as motion-picture files are.

[0060] A still-picture video file under the subdirectory 'STILLDAT', e.g., the file '01001.STL' includes all files of JPEG or TIFF format that would be included under a subdirectory, e.g., '100ABCDE' in DCF structure. All still pictures of DVR's format are also included in the subdirectory 'STILLDAT'.

[0061] In addition, audio contents of the real audio files (\*.rau) and/or the dubbing audio files (\*.dau) may be included in the still picture files (\*.sti). In this case, the real audio files and the dubbing audio files are not created.

[0062] The controller 19 creates a still-picture management file (\*.sti) containing information for search and presentation control of still-picture files (\*.sti) and audio files (\*.rau, \*.dau) under the subdirectory 'STILLDAT' and records it under the subdirectory 'STILLINF' of the 'DVR' directory.

[0063] Thus, a DVR can search for and present a still-picture video (\*.sti), a real-time audio file (\*.rau), and/or a dubbing audio file (\*.dau) under the subdirectory 'STILLDAT' with reference to the recorded still-picture

management file (\*.sti) under the subdirectory 'STILLINF' of the directory 'DVR'.

[0064] If a still-picture video and/or audio file is selected by a playlist file (\*.pls, \*.vpls) containing motion-picture/ still-picture play items, that file is searched for and then presented as explained before.

[0065] Fig. 11 is a data recording structure of a motion-picture recording medium in accordance with the ninth embodiment of the present invention. This embodiment has a sub file structure for still pictures and audio data that is not matched with DCF.

[0066] In this embodiment, still picture files and audio files are recorded altogether under the subdirectory 'STILLDAT' of the directory 'DVR' the same as the eighth embodiment of Fig. 10. However, DVR's still pictures are recorded in the MPEG I-picture format (\*.mpg) or MPEG 2 transport stream format (\*.m2ts) while still pictures of DSC's format are collected into a file with extension of '.sti'.

[0067] Contents of the audio files (\*.rau, \*.dau) may be included in the DVR-formatted still picture files (\*.mpg) or the DSC-formatted still picture files (\*.sti).

[0068] The controller 19 creates a still-picture management file (\*.sti) containing information for search and presentation control of still-picture files (\*.sti), real-time audio files (\*.rau), dubbing audio files (\*.dau), and MPEG-formatted still-picture files (\*.mpg) under the subdirectory 'STILLDAT' and records it under the subdirectory 'STILLINF' of the 'DVR' directory.

[0069] The above-explained method of recording still pictures onto a rewritable recording medium enables a recording medium with motion-picture data recorded by a DVR to accommodate still picture video and audio files in DSC-compatible file system. Thus, file management, e.g., copying, editing, and so on can be conducted efficiently and conveniently through a single recording medium of very large storage capacity, which results in remarkable improvement of use convenience of a motion picture recorder and a digital still camera.

[0070] The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

[0071] In Summary, the present invention relates to a method of recording still pictures and audio data onto a rewritable recording medium. The present method records still-picture video and audio files of the recording format of a digital still camera under a subdirectory of a DCIM (Digital Camera Images) directory of DCF (Design rule for Camera File system) and still-picture video and/or audio files of the recording format of a disk video recorder under a subdirectory of a moving-picture directory, creates management information for searching and

11

EP 1 324 586 A1

12

presentation control of the still-picture video and audio files below the DCIM directory and the still-picture video and/or audio files below the moving-picture directory, and records the created management information under another subdirectory of the moving-picture directory. Thus, efficient and convenient file management is possible through a single recording medium, which results in remarkable improvement of use convenience of a motion picture recorder and a digital still camera.

#### Claims

1. A method of recording still pictures onto a recording medium, comprising the steps of:
  - (a) recording still-picture video and audio files of a recording format of a digital still camera under a subdirectory of a first directory and still-picture video and/or audio files of a recording format of a disk video recorder under a subdirectory of a second directory other than the first directory; and
  - (b) creating management information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory and the still-picture video and/or audio files under the subdirectory of the second directory, and recording the created management information under a subdirectory of the second directory.
2. The method of claim 1, wherein the first directory is a DCIM (Digital Camera Images) directory defined in DCF (Design rule for Camera File system) adopted by a digital still camera.
3. The method of claim 2, wherein the still-picture video and audio files are recorded under respective subdirectories in accordance with the DCF structure.
4. The method of one of claims 1 to 3, wherein the management information is written under a different subdirectory that the still-picture video and/or audio files of a recording format of a disk video recorder are recorded under.
5. The method of one of claims 1 to 4, wherein a dubbing audio file associated with a still picture or pictures is written under the same subdirectory that the still-picture video and audio files of a recording format of a digital still camera or the still-picture video and/or audio files of a recording format of a disk video recorder are recorded under.
6. The method of one of claims 1 to 5, wherein said
- step (a) further records audio files of the recording format of a disk video recorder under the same subdirectory of the second directory that the still-picture video and/or audio files of the recording format of a digital still camera are recorded under.
7. The method of one of claims 1 to 6, wherein parent directory of the first and the second directory is a root directory.
8. The method of one of claims 1 to 6, wherein the first directory is a child directory of the second directory.
9. The method of one of claims 1 to 8, wherein the still-picture video files under the subdirectory of the first directory have extension of 'jpg' or 'tif' and the still-picture audio files under the same subdirectory have extension of 'wav' representing PCM-encoded.
10. The method of one of claims 1 to 9, wherein the still-picture video and/or audio files under the subdirectory of the second directory have data encoded by MPEG standard.
11. A method of recording still pictures onto a recording medium, comprising the steps of:
  - (a) recording still-picture video and audio files under a subdirectory of a first directory; and
  - (b) creating management information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory, and recording the created management information under a subdirectory of a second directory.
12. The method of claim 11, wherein said step (a) further records still-picture audio files of a recording format of a disk video recorder under a subdirectory of the second directory.
13. The method of claim 11, wherein said step (a) further records still-picture audio files of a recording format of a disk video recorder under a subdirectory of the first directory.
14. The method of claim 13, wherein the still-picture audio files under the subdirectory of the first directory are encoded by MPEG standard.
15. The method of one of claims 11 to 14, wherein the first directory is a DCIM (Digital Camera Images) directory defined in DCF (Design rule for Camera File system) adopted by a digital still camera.
16. The method of claim 15, wherein the still-picture vid-

13

EP 1 324 586 A1

14

eo and audio files are recorded under respective subdirectories in accordance with the DCF structure.

ond directory, and recording the created management information under a subdirectory of the second directory.

17. The method of one of claims 11 to 16, wherein parent directory of the first and the second directory is a root directory.

5 26. A recording medium, including a data file and a management information file that are recorded by the following steps of:

18. The method of one of claims 11 to 17, wherein the still-picture video files under the subdirectory of the first directory have extension of 'jpg' or 'tif' and the still-picture audio files under the same subdirectory have extension of 'wav' representing PCM-encoded.

10 recording still-picture video and audio files under a subdirectory of a first directory; and

19. The method of one of claims 11 to 18, wherein the first and the second directory are the same child directory of a root directory.

15 creating management information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory, and recording the created management information under a subdirectory of a second directory.

20. The method of claim 19, wherein the still-picture video and audio files have data encoded by MPEG standard.

20

21. The method of claim 19, wherein the still-picture video and audio files have data that are encoded in a recording format of a digital still camera.

25

22. The method of one of claims 11 to 21, wherein the still-picture audio files under the subdirectory of the first directory have dubbed audio data associated with still pictures.

30

23. The method of one of claims 11 to 22, wherein each of the still-picture video files under the subdirectory of the first directory is composed of at least one picture.

35

24. The method of one of claims 11 to 23, wherein said step (a) writes still-picture video and audio data in a single file together.

40

25. A recording medium, including a data file and a management information file that are recorded by the following steps of:

45

recording still-picture video and audio files of a recording format of a digital still camera under a subdirectory of a first directory and still-picture video and/or audio files of a recording format of a disk video recorder under a subdirectory of a second directory other than the first directory; and



50

creating management information for searching and presentation control of the still-picture video and audio files under the subdirectory of the first directory and the still-picture video and/or audio files under the subdirectory of the sec-

55



EP 1 324 586 A1



EP 1 324 586 A1

FIG. 3





FIG. 4



EP 1 324 586 A1

FIG. 5





FIG. 6



EP 1 324 586 A1

FIG. 7








FIG. 8



EP 1 324 586 A1



EP 1 324 586 A1



EP 1 324 586 A1

European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 02 8879

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	ROBERT MENTA: "Archos Jukebox Multimedia" MP3NEWSWIRE.NET, [Online] 14 December 2001 (2001-12-14), XP002238538 Retrieved from the Internet: <URL:www.mp3newswire.net> [retrieved on 2003-04-16] * page 8, section 6 and page , section 8*	1-26	H04N1/21
X	EP 1 107 103 A (CANON KK) 13 June 2001 (2001-06-13) * abstract * * column 12, line 19 - line 36 * * figure 7 *	1-26	
X	US 2001/040862 A1 (MIMURA HIDEKI ET AL) 15 November 2001 (2001-11-15) * abstract * * page 18, line 0417 - page 19, line 0418 * figure 16 *	1-26	
X	US 6 115 035 A (COMPTON CHARLES L ET AL) 5 September 2000 (2000-09-05) * abstract * * figure 3 * * column 4, line 43 - line 65 *	1-26	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04N
X	WO 01 11626 A (MATSUSHITA ELECTRIC IND CO LTD) 15 February 2001 (2001-02-15) & EP 1 209 680 A (MATSUSHITA) 29 May 2002 (2002-05-29) * abstract * * page 15, line 18 - line 27 * * figure 19 *	1-26	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 April 2003	Examiner Stoffers, C
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons & : member of the same patent family, corresponding document			

BPO FORM 1603 03 02 P04C01

EP 1 324 586 A1

European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 02 8879

## DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	<p>"Design rule for Camera File System" JAPAN ELECTRONIC INDUSTRY DEVELOPMENT ASSOCIATION STANDARD, [Online] December 1998 (1998-12), pages 1-37, XP002238521 Retrieved from the Internet: &lt;URL:http://it.jeita.or.jp/jhistory/document/standard/exif_eng/jeida49eng.htm&gt; [retrieved on 2003-04-16] * figure 3.3 *</p> <p>-----</p>	1-26	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>16 April 2003</b>	Examiner <b>Stoffers, C</b>
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 (03.02.02) (p.00/01)



EP 1 324 586 A1

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 8879

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-04-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 1107103	A	13-06-2001	JP	2001222504 A	17-08-2001
			CN	1300022 A	20-06-2001
			EP	1107103 A2	13-06-2001
			US	2001002846 A1	07-06-2001
US 2001040862	A1	15-11-2001	JP	3382159 B2	04-03-2003
			JP	2000057746 A	25-02-2000
			US	2002159761 A1	31-10-2002
			US	2002159762 A1	31-10-2002
			US	2002154894 A1	24-10-2002
			US	2003016950 A1	23-01-2003
			US	2002114617 A1	22-08-2002
			US	6215746 B1	10-04-2001
US 6115035	A	05-09-2000	AU	7714298 A	10-02-1999
			WO	9904567 A2	28-01-1999
WO 0111626	A	15-02-2001	AU	6183400 A	05-03-2001
			CN	1377502 T	30-10-2002
			EP	1209680 A1	29-05-2002
			WO	0111626 A1	15-02-2001

EPO FORM P0453

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82